



LASER MARKED  
**ORBIS**  
 15 kV 55-3  
 IP15C-1S  
 MM/YYYY



NOTES:  
 MATERIAL: UV RESISTANT HDPE  
 NECK DESIGNATION: C  
 ELECTRICAL APPLICATION: 15kV  
 CREEPAGE DISTANCE: 245mm  
 DRY-ARC DISTANCE: 140mm  
 FLASHOVER 60 HZ:  
 WET: 35kV  
 DRY: 65kV  
 IMPULSE FLASHOVER VOLATGE:  
 POS.: 100kV  
 NEG.: 130kV  
 LOW FREQUENCY PUNCTURE 90kV  
 RIV 50  
 CANTILEVER LOAD: 11KN

THIS DRAWING  
 CONTAINS  
 CONFIDENTIAL  
 INFORMATION  
 AND IS THE  
 EXCLUSIVE  
 PROPERTY OF  
 ORBIS  
 MANUFACTURING

**ORBIS**

DRAWN	MSM	DATE	27-10-2025
APPROVED	RD	DATE	31-10-2025
REVISION	-	-	-

**DRAWING NUMBER**

IP15C-1S

**DESCRIPTION**

INSULATOR PIN 15KV C NECK FOR 1"  
 PIN (ANSI 55-3)